

www.altus-inc.com sales@altus-inc.com

An intelligent approach to **24/7 power.**

Altus powered carts have the ability to power up technology components even while charging. The AC power system on both the Clio and ClioAir keep the workstations and clinician workflows optimized for their entire shifts.

Uninterrupted Workflow

With the LiFePO4 45 Amp/hr. battery that is present on every Altus powered cart, caregivers can work with confidence knowing their workstation will last their entire shift. Clinicians and nurses alike are able to experience an uninterrupted workflow while helping their patients.

On-board Charging

Using on-board charging through wall outlet power, the system powers both the technology components and recharges the battery simultaneously. On average Altus carts are recharged within 2 hours, so no cart is unusable for long periods of time.

Introducing ClioAir

20% lighter, 3 times easier to roll.

The ClioAir is designed with the same powerful features as Clio, but even lighter. It utilizes the same LifePO4 battery to keep workflows uniterrupted. Both Clio and ClioAir feature 18" of sit-to-stand height adjustment, a one-piece design keyboard with a breakaway hinge, and secure technology storage.

ClioAir was engineered to be just as long lasting as our original powered cart. Built from die-cast aluminum, a long lasting battery, and an ergonomic design, ClioAir can handle any workflow a clinician may have for years to come.



20% - &









CART WEIGHT: 97 lbs. WORKSURFACE DIMENSIONS: 20"D x 21"W	CART WEIGHT: 86 lbs. WORKSURFACE DIMENSIONS: 17"D x 20"W
 BATTERY: LiFeP04 Battery System w/ Plug to Charge 586Wh Rechargeable Battery 12.8V(45 AH, LiFeP04) Battery Weight: 12.8 lbs 14 Hours Run Time (Assume constant 40W output) 	 BATTERY: LiFeP04 Battery System w/ Plug to Charge 586Wh Rechargeable Battery 12.8V(45 AH, LiFeP04) Battery Weight: 12.8 lbs 14 Hours Run Time (Assume constant 40W output)
ON-BOARD CHARGING:Approximately 2 hours	ON-BOARD CHARGING:Approximately 2 hours
CHARGER: 15.5 Amp charge	CHARGER: 15.5 Amp charge
• UL/EN60601-1, UL1778, CSAC22-2, EN62040	CERTIFICATIONS:UL/EN60601-1, UL1778, CSAC22-2, EN62040
 USER INTERFACE Handle Mounted User Interface, On/Off and Mute button 	FUEL GAUGE:Handle Mounted User Interface, On/Off and Mute button
POWER CORD:AC-IN: Coiled 7' 5"AC-OUT: 3-Plug	POWER CORD:AC-IN: Coiled 7' 5"AC-OUT: 3-Plug
Inside Base	Inside Base
 WARRANTY: (https://www.altus-inc.com/legal/warranty) 2,500 cycles or 3 years *Cycles defined by battery manufacturer 24 Month Electrical Warranty 	 WARRANTY: (https://www.altus-inc.com/legal/warranty) 2,500 cycles or 3 years *Cycles defined by battery manufacturer 24 Month Electrical Warranty



CART OPTIONS

POWER


C1- Clio Laptop Cart



E1- Clio Laptop Cart with electric lift



C3- Clio LCD Cart



E3- Clio LCD Cart with electric lift

Battery Chemistry LiFe (Lithium Iron Phosphate)

Capacity 45 Amp Hr



Cliquir CART OPTIONS



L3 - ClioAir LCD and All-in-One PC Cart



EL3 - ClioAir LCD and All-in-One PC Cart with electric lift

